

## EC/EU Declaration of Conformity

Nr : BQT8466400-00

**Products identification :**

Type of products : Safety limit switches

Trademark : **Telemecanique Sensors**

Models : **XCSMP...**  
(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following European Directive(s) :

Machinery Directive : **2006/42/EC**

Low Voltage Directive : **2014/35/EU**

EMC Directive : **2014/30/EU**

RoHS Directive : **2011/65/EU + 2015/863**

Product's conformity has been assessed by applying the following harmonized standard(s) :

**EN ISO 13849-1:2015**

**EN ISO 14119:2013**

**EN 60204-1:2018**

**EN 60947-5-1:2017 + AC:2020**

**EN IEC 62061:2021**

**EN IEC 63000:2018**

When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.

**Gregory POUX**

Customer Satisfaction & Quality Director

Issued at : L'Isle d'Espagnac – FRANCE

Emission date : January 30<sup>th</sup>, 2024



Type text here

**TMSS France**

Postal address :  
Tour Egho – 2 avenue Gambetta  
92400 Courbevoie – FRANCE

<https://tesensors.com/global/en/support/technical-support>

**Technical Documentation authority :**

**TMSS France**  
Boulevard Salvador Allende – ZI n° 3  
16340 L'Isle d'Espagnac – FRANCE

## Appendix

Nr : BQT8466400-00

List of product models covered by the present EC/EU Declaration of Conformity

<b>XCSM</b>	<b>P</b>	<b>59</b>	<b>L2</b>
<b>I</b>	<b>II</b>	<b>III</b>	<b>IV</b>

<b>I</b>	<b>Product type</b>		
	<b>XCSM</b>	:	Key operated safety switch (without locking of the key)
<b>II</b>	<b>Body type</b>		
	<b>P</b>	:	Plastic
<b>III</b>	<b>Contacts type</b>		
	<b>59</b>	:	1 NC + 1 NO, slow break (break before make)
	<b>70</b>	:	2 NC + 1 NO, slow break (break before make)
	<b>79</b>	:	2 NC, slow break
	<b>80</b>	:	3 NC, slow break
<b>IV</b>	<b>Cable type and length</b>		
	<b>L••</b>	:	Standard flexible cord (PVC insulation), axial output (•• = one or two digits giving the cable length in meter)

**NOTE** : These references may be followed by 1 to 3 alphanumeric digits, to denote assembly, marking or packaging variations, without impact on products characteristics and/or compliance.