

EU Declaration of Conformity

Nr : BRU8683600-00**Products identification :****Type of products :** Inductive proximity switches for rotation monitoring**Trademark :** **Telemecanique Sensors****Models :** **XSAV...**
(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following European Directive(s) :

Low Voltage Directive : **2014/35/EU**EMC Directive : **2014/30/EU**RoHS Directive : **2011/65/EU + 2015/863**

Product's conformity has been assessed by applying the following harmonized standard(s) :

EN IEC 60947-5-2:2020**EN IEC 63000:2018**

When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.

Gregory POUX

Customer Satisfaction & Quality Director

Issued at : L'Isle d'Espagnac – FRANCE**Emission date :** December 6th, 2024**TMSS France**Postal address :
Tour Egho – 2 avenue Gambetta
92400 Courbevoie – FRANCE<https://tesensors.com/global/en/support/technical-support>**Technical Documentation authority :****TMSS France**
Boulevard Salvador Allende – ZI n° 3
16340 L'Isle d'Espagnac – FRANCE

Appendix

Nr : BRU8683600-00

List of product models covered by the present EU Declaration of Conformity

XSAV	1	1	373	L05	TF	TQ
I	II	III	IV	V	VI	VII

I	Product type	
	XSAV	: Inductive proximity switches for rotation monitoring
II	“Run-up” delay following power-up	
	0	: Without “run-up” delay
	1	: Normal “run-up” delay (9 s)
	3	: Reduced “run-up” delay (3 s)
III	Adjustable frequency range	
	1	: 6...150 impulses/min
	2	: 120...3000 impulses/min
IV	Wiring scheme and output type	
	373	: DC 3 wires, with PNP output
	801	: AC/DC 2 wires, with static output
V	Additional digit for specific cable length	
	Blank	: Standard flexible cord (PVC insulation), 2 m length
	L••	: Standard flexible cord (PVC insulation) (•• = one or two digits giving the cable length in meter)
VI	Additional digit for specific temperature range	
	Blank	: Version for standard temperatures (-25...+70 °C)
	TF	: Specific version for low temperatures (-40 °C)
	TT	: Specific version for high temperatures (+85 °C)
VII	Additional suffix for specific packaging	
	Blank	: Normal packaging (unitary)
	TQ	: Bulk packaging (this suffix only appears on the bulk packaging label, it does not appear on the product)

NOTE : These references may be followed by 1 to 3 alphanumeric digits, to denote assembly, marking or packaging variations, without impact on products characteristics and/or compliance.

TMSS France

Postal address :
Tour Egho – 2 avenue Gambetta
92400 Courbevoie – FRANCE

<https://tesensors.com/global/en/support/technical-support>

Technical Documentation authority :

TMSS France
Boulevard Salvador Allende – ZI n° 3
16340 L'Isle d'Espagnac – FRANCE