

SR D50 1950 FS22 16 10 2500 DSH GFK AL (105 281)



Figure without obligation

Supporting tube with internal sealing end and air-termination rod Ø22/16/10 mm.

Type	SR D50 1950 FS22 16 10 2500 DSH GFK AL
Part No.	105 281
Material of air-termination rod	Al
Length of air-termination rod	2500 mm
Material of supporting tube	GRP / Al
Length of supporting tube	1955 mm
Transport length	2500 mm
External diameter Ø	50 mm
Length of insulation clearance	1560 mm
Wall thickness	4 mm
Material factor km	0.7
Permanent temperature range	-50 °C ... +100 °C
Type	UV-stabilised
Sleeve	60 x 5 mm
Max. gust wind speed	140 km/h
Pull-out force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Bending force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	4 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364260962
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.