

DCU 2 YPV 1100 2M 2S (900 923)






Figure without obligation



Basic circuit diagram DCU 2 YPV 1100 2M 2S



Dimension drawing DCU 2 YPV 1100 2M 2S

Generator junction box for PV systems of up to 1100 V DC for protecting two MPP inputs and two strings each. With surge protection and push-in terminals for the input and output.

Type	DCU 2 YPV 1100 2M 2S
Part No.	900 923
SPD according to EN 61643-31 / IEC 61643-31	type 2 / class II
Max. PV voltage (U _{CPV})	1100 V
Short-circuit current rating (I _{SCPV})	10 kA
Total discharge current (8/20 μs) (I _{total})	40 kA
Nominal discharge current (8/20 μs) [(DC+/DC-) --> PE] (I _n)	20 kA
Max. discharge current (8/20 μs) [(DC+/DC-) --> PE] (I _{max})	40 kA
Voltage protection level (U _p)	≤ 4 kV
Nominal load current (I _L)	40 A
Response time (t _A)	≤ 25 ns
Operating temperature range (T _U)	-35°C to +60°C
Operating state / fault indication	green / red
Number of ports	1
cross-sectional area (⌀) (min.)	6 mm ²
cross-sectional area (⌀) (max.)	16 mm ² solid / 25 mm ² fine-stranded
cross-sectional area (DC+, DC-) (min.)	2.5 mm ² fine-stranded
Cross-sectional area (DC+, DC-) (max.)	6 mm ² fine-stranded
Place of installation	outdoor
Degree of protection	IP 65
Rated insulation voltage (DC) (U _i)	1500 V
Type	with pressure compensating element
Cover	transparent cover with product label
Colour of enclosure	grey
Number of cable entries	4x 3-fold screw connection
Number of cable entries	2x M20
Weight	1,74 kg
Customs tariff number (Comb. Nomenclature EU)	85372091
GTIN	4013364492400
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.