

SITOR cylindrical fuse link, 10 x 38 mm, 25 A, aR, Un AC: 600 V, Un DC: 700 V, DC according to UL



Model	
product brand name	SETRON
product designation	SITOR cylindrical fuse link
design of the product	DC acc. to UL
General technical data	
operating class of the fuse link	aR
size of the fuse link	10x38 mm
type of voltage	AC
operating current / at AC / rated value	25 A
supply voltage / at DC	700 V
operating voltage / rated value	600 V
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	6 W
Main circuit	
operating current	
• rated value	25 A

Product details

product component / striker No

Mechanical Design

mounting position Any, preferably vertical

net weight 9 g

Certificates

reference code

• acc. to DIN EN 61346-2

F

• acc. to DIN EN 81346-2

F

General Product Approval

Declaration of Conformity



CCC



CSA



UR

[Miscellaneous](#)



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1025>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC1025>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1025

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



