

Safety transformer, 40VA Primary 230 V AC, 50Hz, secondary 2x12 V/24 V AC With PTC fuse, 5 MW++



Model	
Product brand name	SETRON
Product designation	Safety transformer
Design of the transformer	Safety transformer
General technical data	
Supplied active power / maximum	40 W
Voltage	
Input voltage	230 V
Output voltage	
• _1 / rated value	12 V
• _2 / rated value	24 V
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	8 W
Current	
Output current	
• maximum	3.3 A

- \_1 / rated value 3.3 A
- \_2 / rated value 1.6 A

### Suitability

#### Suitability for integration

- surface-mounted installation No
- flush mounting No

### Product details

Product component / switch No

### Product function

Product function / Thermal protection Yes

### Inputs Outputs

Property of the output / Short-circuit proof Yes

### Mechanical Design

Height	64 mm
Width	90 mm
Length	90 mm
Number of width units	5
Mounting type / Side-by-side mounting	Yes

### Certificates

**Declaration of Conformity**

other

[Confirmation](#)



EG-Konf.

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AC3740-0>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4AC3740-0>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=4AC3740-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AC3740-0)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

<http://www.siemens.com/specifications>

