



MINIZED, Switch disconnector with Fuse, D02, 3-pole, In: 63 A, Un AC: 400 V

Model					
product brand name		MINIZED			
product designation		Switch disconnectors with fuses			
General technical data					
number of poles		3			
size of fuse system / acc. to DIN EN 60269-1		D02			
overvoltage category		4			
Voltage					
surge voltage resistance / rated value		6 kV			
Supply voltage					
operational current / at AC / rated value		63 A			
operating voltage / at AC / rated value		400 V			
Protection class					
protection class IP		IP20, with connected conductors			
Dissipation					
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole		7.5 W			
Product details					
product feature / sealable		Yes			
Connections					
tightening torque / with screw-type terminals					
• minimum		2.5 N·m			
• maximum		3 N·m			
Mechanical Design					
height		70 mm			
width		81 mm			
depth		90 mm			
mounting position		any, preferably vertical			
net weight		455 g			
Certificates					
reference code					
• acc. to DIN EN 61346-2		F			
• acc. to IEC 81346-2		F			
General Product Approval		Declaration of Conformity	Test Certificates	Marine / Shipping	other



[Type Test
Certificates/Test
Report](#)



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG7133>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SG7133>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SG7133

Tender specifications

<http://www.siemens.com/specifications>



