

DELTA connection socket Universal connection unit 2x 8-pole RJ45
Cat. 6 A unshielded LSA-plus terminals Screw mounting



Figure similar

Model	
Product brand name	DELTA
Product designation	Connection socket
Design of the product	Communication
Type of composition	basic element
General technical data	
Mounting type	fixing with screw
Surface processing	others
Product feature / Printed marking	No
Material	others
Protection class	
Protection class IP	IP20
Suitability	
Suitability for operation	universal connection unit/ISDN connection unit
Appearance	
Appearance	not applicable

Color	miscellaneous
-------	---------------

Product details

Product feature	
<ul style="list-style-type: none"> • Luster terminal • Dust cover 	<p>No</p> <p>No</p>
Product component	
<ul style="list-style-type: none"> • Labeling field • Hinged lid • strain relief 	<p>No</p> <p>No</p> <p>No</p>
Product feature	
<ul style="list-style-type: none"> • halogen-free • transparent 	<p>Yes</p> <p>No</p>

Mechanical Design

Height	70 mm
Depth	28 mm
Mounting type	flush mounted
Material	plastic

Certificates

Declaration of Conformity



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TG2027-2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TG2027-2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TG2027-2

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>