# **SIEMENS**

## Data sheet

# 5UB1915

DELTA i-system titanium white SCHUKO socket outlet 10/16 A 250 V With screwless Connection terminals with spring flap 55x 55 mm and increased touch protection



Model	
Product brand name	DELTA
Product designation	SCHUKO socket outlet
Cover version	central plate
Design of the special power supply unit	without special current supply
Design of the socket / according to VDE 0620 for severe conditions	No
Design of the phase tap	No
General technical data	
Marking / of socket outlet	without imprint
Mounting type	fixing with claw and screw
Surface processing	others
Material	thermoplastic
Supply voltage	
Operating voltage / Rated value	250 V
Protection class	
Protection class IP	IP20
Main circuit	

Rated value  Appearance Color  Product details  Product component      Ejection equipment      Labeling field      Increased touch protection      Fault current protection      miniature fuse      Integrated / functional lighting      Integrated / Light source	16 A white No No Yes No No No No No
Color Product details Product component • Ejection equipment • Labeling field • Increased touch protection • Fault current protection • miniature fuse • Integrated / functional lighting	No No Yes No No No No
Color Product details Product component • Ejection equipment • Labeling field • Increased touch protection • Fault current protection • miniature fuse • Integrated / functional lighting	No No Yes No No No No
Product component • Ejection equipment • Labeling field • Increased touch protection • Fault current protection • miniature fuse • Integrated / functional lighting	No Yes No No No
Product component • Ejection equipment • Labeling field • Increased touch protection • Fault current protection • miniature fuse • Integrated / functional lighting	No Yes No No No
<ul> <li>Labeling field</li> <li>Increased touch protection</li> <li>Fault current protection</li> <li>miniature fuse</li> <li>Integrated / functional lighting</li> </ul>	No Yes No No No
<ul> <li>Increased touch protection</li> <li>Fault current protection</li> <li>miniature fuse</li> <li>Integrated / functional lighting</li> </ul>	Yes No No No
<ul> <li>Fault current protection</li> <li>miniature fuse</li> <li>Integrated / functional lighting</li> </ul>	No No No
<ul> <li>miniature fuse</li> <li>Integrated / functional lighting</li> </ul>	No No No
<ul> <li>Integrated / functional lighting</li> </ul>	No No
	No
Integrated / Light source	
	No
<ul> <li>Integrated / orientation lighting</li> </ul>	NO
Hinged lid	Yes
Product feature	_
lockable	No
● halogen-free	Yes
• transparent	No
Product function	
Product function	
Socket selectable	No
<ul> <li>Overvoltage protection</li> </ul>	No
Number	
Number of units	1
Number of sockets / switchable	0
Connections	
Arrangement of contacts / diagonal	No
Type of electrical connection	plug terminal
Mechanical Design	
Height	70 mm
Width	70 mm
Depth	45 mm
Mounting type	flush mounted
Material / of the enclosure	plastic
Certificates	

## **General Product Approval**





**Declaration of Conformity** 



#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5UB1915

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/5UB1915

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=5UB1915

### **CAx-Online-Generator**

http://www.siemens.com/cax

#### **Tender specifications**

http://www.siemens.com/specifications

