

SIMATIC S7-1500, Front connector in push-in design, 40-pole for 25 mm wide modules and compact CPUs of the S7-1500, incl. cable tie

General information	
Product type designation	Front connector
Connection method	
Connection I/O signals	
<ul style="list-style-type: none"> <li>• Connection method</li> <li>• Number of lines per connection</li> </ul>	Push-in terminal 1; or max. 8x 2 conductors to 1.5 mm <sup>2</sup> (in total) in a shared end sleeve and max. 32x 0.75 mm <sup>2</sup> single core
Conductor cross-section in mm <sup>2</sup>	
— Connectable cable cross-sections for massive cables, min.	0.25 mm <sup>2</sup>
— Connectable cable cross-sections for massive cables, min.	1.5 mm <sup>2</sup> ; max. 32x 0.75 mm <sup>2</sup> , 8x 1.5 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables without end sleeve, min.	0.25 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables without end sleeve, max.	1.5 mm <sup>2</sup> ; max. 32x 0.75 mm <sup>2</sup> , 8x 1.5 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables with end sleeve, min.	0.25 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables with end sleeve, max.	1.5 mm <sup>2</sup> ; max. 32x 0.75 mm <sup>2</sup> , 8x 1.5 mm <sup>2</sup>
Conductor cross-section acc. to AWG	
— Connectable cable cross-sections for massive cables, min.	24
— Connectable cable cross-sections for massive cables, min.	16; max. 32x AWG 19, 8x AWG 16
— Connectable cable cross-sections for flexible cables without end sleeve, min.	24
— Connectable cable cross-sections for flexible cables without end sleeve, max.	16; max. 32x AWG 19, 8x AWG 16
— Connectable cable cross-sections for flexible cables with end sleeve, min.	24
— Connectable cable cross-sections for flexible cables with end sleeve, max.	16; max. 32x AWG 19, 8x AWG 16
Wire end processing	
— Stripped length of cables, min.	8 mm
— Stripped length of cables, max.	11 mm

— End sleeve acc. to DIN 46228 without plastic sleeve

Form A, 10 mm long

— End sleeve acc. to DIN 46228 with plastic sleeve

Form E, 8 mm and 10 mm long

#### Mounting

— Tool

Screwdriver, conical design, 3 mm to 3.5 mm

#### Dimensions

Width 19.8 mm

Height 130.5 mm

Depth 43 mm

#### Weights

Weight, approx. 123 g

**last modified:** 11/16/2020